

117 LMN Silicone

Perimeter sealing of windows & door frames.

With its excellent adhesion to virtually all construction materials, easy application and permanent elasticity with movement amplitude of up to 20%, Xpert 117 LMN silicone is ideally suited to sealing all kinds of building joints and edges inside and out, especially around door and window frames.

- 1-component neutral silicone sealant
- Very easy to apply with the Xpert heavy duty Dripless Mastic gun
- Excellent adhesion to almost all building materials (see technical datasheet online)
- Permanent elasticity
- For outdoor and indoor applications
- High resistance to ageing, weathering and UV
- Temperature resistance: -50°C - +150°C
- Skin formation time: 15 mins at 23°C and 50% relative humidity
- Curing rate: 2.5 – 3mm after 24h at 23°C and 50% relative humidity
- MEKO-free - contains no Methyl Ethyl Ketoxime (MEKO) which is considered hazardous. This makes it odourless and safer for you and your customers.
- Available in Snow White, Brown RAL 8017, Black RAL 9005, Clear and Anthracite Grey RAL 7016



Colour	RAL	Size	Part Code	Box Qty.
Snow White	-	280ml	SIL20000	12
Clear	-	280ml	SIL20006	12
Brown	RAL8017	280ml	SIL20002	12
Black	RAL9005	280ml	SIL20005	12
Anthracite Grey	RAL7016	280ml	SIL20007	12

Scan the QR code for our Technical Data Sheet

